

RANGER® R3D

Dual mode, perimeter surveillance radar

APPLICATIONS


BORDER SECURITY

**INDUSTRIAL FACILITY
SECURITY**

**MONITOR PORTS,
AIRPORTS, & MILITARY
BASES**

**CRITICAL
INFRASTRUCTURE
PROTECTION**

FORCE PROTECTION



The Ranger R3D is a dual mode, ground surveillance radar designed to provide efficient, 24/7 persistent surveillance, both within and beyond the fence. Operating in the Ka-band, the Ranger R3D leverages the resolution and accuracy of advanced FMCW technology and the extended range and terrain adaptability of Doppler in a single, compact, and lightweight package. Ruggedized for permanent, all-weather installations and mobile, stop-and-scan operations, its low minimum detection velocity (MDV) detects slow-moving threats such as walkers and crawlers.

A COTS unit for detecting and tracking surface movement, R3D provides wide area detection when used as a cueing device. Operators can be confident of up to 128 threats at a time due to low false alarm rates. Network with other FLIR radars to create an overlapping array that protects larger areas such as borders, ports, airports, and military bases. Target information output includes ID, location, range, bearing, latitude, longitude, confidence level, heading, speed, and time.

FEATURES

DOPPLER CAPABILITY

Ranger R3D Doppler provides extended range coverage in almost any terrain. Overcome blind target ranges/velocities by switching to Fast Scan/FMCW.

DUAL-MODE CAPABILITY

Switch between Fast Scan and Doppler depending on terrain and recognition requirements. Enhanced performance supports both radial and tangential detection.

INTEGRATED PROTECTION

Network multiple FLIR radars and EO/IR imagers with FLIR command and control to form a single powerful, integrated surveillance system.

FAST, ACCURATE THREAT DETECTION

R3D quickly detects up to 128 threats simultaneously while accurately displaying each target's location.

RUGGEDIZED FOR RIGOROUS DUTY

Designed for permanent, all-weather installations and mobile, stop-and-scan operations, R3D can detect pedestrians, crawlers, and vehicles in virtually any environment.

SPECIFICATIONS

R3D	
Target Types	Moving, Less than 0.1m/s minimum for vehicles and personnel
Target Velocity	0.1 to 50 m/s
Communications	Ethernet, wireless, fiber
XML	Yes (ICD-0100 compliant)
Target Information	Includes: ID; location: range & bearing; latitude & longitude; Confidence level; Heading; Speed; Time

COMMAND & CONTROL	
Scan Rate	3 to 60 rpm, continuous or sector
Elevation Coverage	6°
Elevation Control	Up: 2°; Down: 5° (fixed settings)
Input Power	20 to 32 VDC, 24 nominal
False Alarm Rate	< 1 per 24 hours (Fast Scan)
Mask Zone(s)	One angular detection zone (Doppler) Two selectable angular detection zones (Fast Scan) One selectable angular detection zone (Doppler) Unlimited polygon detection zones

ENVIRONMENTAL	
Network	Up to 8 per server; total unlimited
Dimensions	14.7" h x 18.3" diameter
Weight	29 lbs (14 kg)
Power Consumption	40 watts
Operating Range	5 – 6,500 m
Detection Range	5 – 3,500 m, personnel walking 5 – 6,500 m, vehicles and watercrafts
Coverage Area	133 km ² (53 mi ²)
Temperature	-30° to +65° C (operating) -40° to +70° C (storage)
Humidity	50% to 95%, non-condensing (60° C max)
Altitude	Up to 15 000 ft (operating and storage)
Wind	Up to 140 km/hr
Weather Sealing	IP66 rating
Protocol	ICD-0100

	FAST SCAN (NO DOPPLER)	FAST	DOPPLER INTERMEDIATE	LONG RANGE
Instrument Range	2,800 m	6,500 m	6,500 m	6,500 m
Detection Pedestrian	1,900 m	2,500 m	3,000 m	3,500 m
Detection Light Vehicle	2,500 m	4,300 m	5,000 m	6,000 m



AMERICAS

27700 SW Parkway Ave
Wilsonville, OR 97070

EUROPE

2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom

Antennv gen 6,
PO Box 737
SE-187 66 Täby
Sweden

MIDDLE EAST

Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit /
Khalifa Park Area
Abu Dhabi, U.A.E.

Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia

ASIA

Meguro Tokyo Bldg. 5F,
2-13-17
Kami-Osaki, Shinagawa-ku.
Tokyo, 141-0021, Japan

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited. For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2021 Teledyne FLIR LLC. All rights reserved.

Revised on 09/21/21
RangerR3D_Datasheet-LTR 21-0921